

Blue Horizons

Calcium Hardness Raiser



Key Features

- A calcium flake which rapidly increases calcium hardness
- Part of the B.O.A.S.T. System

Ideal calcium hardness level: min. 200mg/l (ppm)

Incorrect calcium hardness	
Low	High
Corrosive water	Scale formation
Etching of surfaces	Rough surfaces
	Cloudy Water
	Reduced circulation
Add: Calcium Hardness Raiser	Add: Stain & Scale Inhibitor

Application Instructions

1. Before applying this product, it should be pre-dissolved in a clean plastic container at a maximum rate of 100g of product per 2.2 gallons (10 litres) of clean cold water. Stir well to ensure the product is fully dissolved.
2. Add the resulting solution to the pool, near the inlets with the filtration system running.
3. Following the application, the pool water may become cloudy, so keep the filtration running continuously until the water clears.
4. Repeat application to achieve the total dose required. It is recommended that the total amount is split into three equal doses with a minimum of 8 hours between each.
5. After application, check the pH level and if necessary, adjust.

Litres	Gallons	To increase CH by 10mg/l	To increase CH by 25mg/l
4,546	1,000	68g	170g
11,365	2,500	170g	425g
22,730	5,000	340g	850g
45,460	10,000	680g	1.7kg
68,190	15,000	1kg	2.55kg

Warning: Heat is generated when pre-dissolving this product. Always use clean cold water.

